



Mattson Joinery - Care And Handling Of Timber Solid Core Doors And Windows.

Thank you for purchasing a Mattson Joinery Timber Joinery Product.

As Master Joiners you are assured that our products will provide you with the highest standard of quality and service.

To ensure optimum performance of our range of timber joinery products please read the following guidelines and instructions.

Storage and Handling;

Product Type - Mattador™ Interior and Exterior PQ/Timber Veneer Solid Core Doors, Fire Rated Doors, Acoustic Performance Doors, Solid Core Doors.

- Doors must be kept dry and fully undercoated /sealed upon arrival to site.
- Doors must be stored horizontally on a level surface using three same size bearers.
- Doors must be covered at all times and kept away from heat and direct sunlight
- Doors to be stored in a dry position, away from any moisture and variations of humidity and temperature.
- Doors to be lifted in the stack (Do Not Slide)

Product Type - Mattador™ Interior and Exterior PQ/Timber Fire Rated Windows.

- Windows must be kept dry and fully undercoated /sealed upon arrival to site.
- Windows should be stored vertically on a level surface using two or three same size bearers.
- Windows if glazed to be lifted vertically at all times.

Painting and Clear Finish;

Always follow the paint manufacturer's recommendations to achieve the optimal finish. Humidity can cause deterioration of untreated doors over a period of time. A quick drying primer/sealer is recommended to seal the surfaces and edges of the door.

A light sanding between coats removing grain raise will further enhance the final finish. Consult your paint supplier when using water based acrylic paints on door that are in contact with rubber door seals to check compatibility of rubber door seals and paint specification.

As noted above, all doors to have both faces and all four edges sealed prior or immediately upon arrival to site. This is very important especially for timber veneered doors. Failure to seal doors correctly may invalidate the warranty.

Painting dark colours on exterior doors should be avoided as they encourage heat absorption which can lead to distortion of the door leaf.

Because the application of finishes is beyond the control of Mattson Joinery, no liability is accepted for the quality of the finished result.

Care and Maintenance;

To maintain your door we recommend you inspect it regularly (every 6 months). Dust and wipe down with a damp cloth. Repair any scratches or breakages to the protective finish. Doors installed in areas subject to dampness, e.g. bathrooms etc any breakages to the protective coating must be repaired immediately. All maintenance painting or clear finishing must be in accordance with instructions of the coating manufacturer.

Entry Doors – Oil Tempered Skinned Hardboard Doors / Marine Ply Skinned Doors

These doors **MUST** be protected from the direct elements and should be coated (both faces and four edges) in light reflective colours. Dark colours are **NOT** recommended. Failure to comply with these requirements will **VOID** the manufacturer's warranty.

Cropping for hardware to be fully spot primed and fitted with appropriate door hardware with weathering seals.

Please See Over.



Fire Rated Doors - Mattador™ Interior / Exterior Doors.

Mattador™ fire door approvals allow a maximum 2.5 mm gap between the door leaf and the approved door frame / jamb (Sides and Head). A 10mm maximum gap between the underside of the door leaf and the top of the finished flooring is permitted.

Refer to the Mattador™ Approved **Fire Rated Hardware List** (FRHL) for a selection of approved closers, latches and misc hardware. The installation of non approved hardware will void the rating of the door system. Mattson Joinery will not be responsible for non compliant door systems.

Fire tags are issued for each specific Mattador™ doorset on receipt of the signed and completed Hardware **Declaration List** (HDL) All Mattson Joinery Fire Door Systems require the appropriate tags to be affixed to the door leaf and door frame.

No modifications / alterations are to be made to the Mattador™ door system after installation of the tags. (E.g.; penetrations for pet doors etc)

Exterior doors **MUST** be protected from the direct elements and should be coated (both faces) in light reflective colours. Dark colours are **NOT** recommended. Failure to comply with these requirements will **VOID** the manufacturer's warranty.

Warranty

We are pleased to advise that Mattson Joinery Mattador™ products comply durability requirements of the New Zealand building code clause B2 durability.

Interior Non Rated Doors – 5 Years

Exterior Non Rated Doors, Interior Fire Rated Doors, Exterior Fire Rated Doors – 15 Years

We are also pleased to offer a two year warranty period of 2 years from date of installation, against defects in materials and workmanship.

The above information is current at time of printing. Mattson Joinery reserves the right to update this information as required.

B Mattson Ltd – March 2023

End of Document.

