

Mattson Joinery - Mattador™ Approved (FRHL) Fire Rated Hardware List



The following hardware options have been approved for use on Mattson Joinery **Mattador™** Fire Door Systems only.

Competitive prices to supply the following hardware components are available upon request.

A factory cropping service for mortice locks on our CNC routing machine is available, this ensures compliance and saves time on site.

All site cropping on porch grade exterior doors MUST be primed.

	30min	60min
<u>CLOSERS</u>		
Briton 1120, 1130,	✓	✓
Dorma TS68, TS73, TS77, TS83, TS85, TS92,TS93.	✓	✓
Guardsman G1300, G1500, G3003	✓	✓
LCN 4031,1460, 1461, 4000, 4041,524	✓	✓
Lockwood 2024, 2516, 3024, 7726, 7714, 7724.	✓	✓
Kaba 9000 Series 9024	✓	✓
MBC 525, 527	✓	✓
ISEO 60, 110, 310, 115, 315, 9100	✓	✓
Record DFA127	✓	✓
<u>DOUBLE ACTION</u>		
Ryobi 8853, 1550, 2550, 3550, 4550	✓	✓
Briton 2800 adjust/strength Transom Closer	✓	x
Dorma BTS85 Floor Spring	✓	x
Dorma RTS85 Transom Closer	✓	x
Lockwood 7750 Floor Spring	✓	x
Lockwood 9800N Tansom Closer	✓	x
Ryobi 202K Floor Spring	✓	x
Ryobi 30-31 Transom Closer	✓	x
<u>HOTEL</u>		
Kaba 790 ASM	✓	✓
Kaba 790 Cylinder Lock	✓	x
Miwa Brantas AL5H	✓	✓
Saflok MT with A59840 mortice lock	✓	✓
Vingcard	✓	✓
<u>TUBULAR</u>		
Dalco 12002 Tubular latch	✓	✓
Lockwood 530 tubular latch	✓	✓
Lockwood 8530 headlatch	✓	✓
Miles Nelson 412 tubular latch	✓	✓
<u>ROLLER LATCH</u>		
Dalco 12002 Roller Latch	✓	✓
Erabus E1511 Roller catch	✓	✓
Kaba Boyd RB111 Roller Latch	✓	✓
Miles Nelson 333 Roller catch	✓	✓
UDM Roller Latch	✓	✓
Samson 515 Roller catch	✓	✓
Legge DAX15211 SS	✓	✓
<u>KEY IN KNOB</u>		
Guardsman Key In Knob series	✓	x
Interlock MCN 3082	✓	x
Lockwood KKI	✓	x

	30min	60min
<u>KEY IN LEVER</u>		
Lockwood 530 series	✓	x
Jupiter, Regent	✓	x
Legge G2 Neptune lever series cylindrical	✓	x
Lockwood 930 series	✓	x
Lockwood KL3 / KL5	✓	x
<u>MORTICE</u>		
Dorma ST9604, ST9602	✓	✓
Kaba Boyd MS series MS52 SSS	✓	✓
Legge 990 series	✓	✓
Legge 990 MFE Electronic lock 10mm cable hole	✓	✓
Lockwood 3500 series 3572,3772.	✓	✓
Lockwood 3570 Electronic Lock	✓	✓
Mile Nelson MNC5000	✓	✓
Novas 6000 series	✓	✓
<u>MISC HARDWARE</u>		
Briton 376-378 Series Panic Exit Device	✓	✓
Briton door co-ordinator	✓	✓
Briton magnetic door clamp	✓	✓
Eff Eff 10312-10 Power transfer hinge	✓	✓
Grille - Lorient LVHD Grille	✓	✓
Grille - Tenmat infill 350 x 350	✓	x
Guardzman G70 door viewer	✓	✓
Ives-Cor door co-ordinator	✓	✓
Legge 881 Power Transfer Device ,Legge V31.	✓	✓
Lockwood 8810,8811	✓	✓
Lockwood 160 Door viewer	✓	✓
Lockwood EM600	✓	✓
Raven RP8,RP10, & RP24.	✓	✓
Raven RP38, & RP70	✓	x
Schlage A, AL, F Series	✓	x
Schlage DV004 Door Viewer	✓	✓
Securicraft MC 41PB security chain	✓	✓
Trimec electric strike	✓	x
Von Duprin 22-F + 2227-F series Panic Exit Device	✓	✓
Von Duprin 88 and 8827 series Panic Exit Device	✓	✓
Von Duprin 99-F + 9927-F series Panic Exit Device	✓	✓
Von Durpin EPT Power Transfer Device	✓	✓
V Lock Lockwood	✓	✓

SUMMARY

The installation of **non** approved hardware will **void** the fire rating of the Mattador fire door system.

Mattson Joinery will not be responsible for non compliant door systems.

Fire tags will be issued for each doorset on receipt of the signed and completed (HDL) Hardware Declaration List.

All Mattson Joinery Fire Door Systems require the appropriate tags to be affixed to the door leaf and door frame.

No modifications / alterations are to be made to the door system after installation of tags.eg penetrations for pet doors.

Mattson Joinery fire door approvals allow a maximum 2mm gap between the door leaf and the door frame / jamb

A **10mm maximum** gap between the underside of the door leaf and the top of the finished flooring is permitted

Closers to be non hold open with back check.

Dated August 2021

www.mattsonjoinery.co.nz